

SPHERICAL						
ACUVUE® Products	Daily Disposable			Reusable		
	1-Day ACUVUE® MOIST®	1-Day ACUVUE® MOIST® MULTIFOCAL	ACUVUE® OASYS® 1-Day with HydraLuxe™ Technology	ACUVUE 2®	ACUVUE® OASYS® with HYDRACLEAR® PLUS	ACUVUE® VITA™
Recommended Replacement	1 day	1 day	1 day	2 weeks	2 weeks	1 month
Lens parameters			Lens parameters			
Lens Material	etafilcon A	etafilcon A	senofilcon A	etafilcon A	senofilcon A	senofilcon C
Water Content	58%	58%	38%	58%	38%	41%
Center Thickness (mm @-3.00D)	0.084	0.084	0.085	0.084	0.070	0.070
UV Blocking*	Class 2	Class 2	Class 1	Class 2	Class 1	Class 1
Visibility Tint	Yes	Yes	Yes	Yes	Yes	Yes
Inside Out Mark	Yes ("123")	Yes ("123")	Yes ("123")	Yes ("123")	Yes ("123")	Yes ("123")
BC (mm) / Dia (mm)	8.50/14.2 (10, 30, 90 lenses) 9.00/14.2 (30, 90 lenses)	8.40/14.3	8.50 & 9.00 / 14.3	8.30 & 8.70 / 14.0	8.40 & 8.80 / 14.0	8.40 & 8.80 / 14.0
Spherical Power Range	-0.50D to -12.00D +0.50D to +6.00D (in 0.50D steps above +/- 6.00D)	-9.00D to +6.00D (0.25D steps) ADDS: LOW +0.75D to +1.25D MID +1.50D to +1.75D HIGH +2.00D to +2.50D	-0.50D to -12.00D +0.50D to +8.00D (in 0.50D steps above +/- 6.00D)	-0.50D to -12.00D +0.50D to +8.00D (in 0.50D steps above +/- 6.00D)		
Acuvue Oasys Bandage contact lenses Available in box of 6 lenses 8.40/8.80 & Plano (Zero) Power				All other parameters same as Acuvue Oasys with HydraClear Plus		

ASTIGMATISM						
ACUVUE® Products	Daily Disposable	Reusable Disposable		Power range of Acuvue products for Astigmatism		
	1-Day ACUVUE® MOIST® for ASTIGMATISM	ACUVUE® OASYS® for ASTIGMATISM	ACUVUE® VITA™ for ASTIGMATISM	1 Day Acuvue Moist for Astigmatism	Acuvue Vita for Astigmatism	Acuvue Oasys for Astigmatism
Recommended Replacement	1 day	2 weeks	1 month	Low Minus Sph powers	Plano to -6.00D (0.25D steps)	Plano to -6.00D (0.25D steps)
Lens parameters				Cylindrical power	-0.75D, -1.25D and -1.75D	-0.75D, -1.25D, -1.75D, -2.25D and -2.75D
Lens Material	etafilcon A	senofilcon A	senofilcon C	Axis	10° to 180° (10° increments)	10° to 180° (10° increments)
Water Content	58%	38%	41%	Cylindrical power	-2.25D	
Center Thickness (mm @-3.00D)	0.090	0.080	0.080	Axis	10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
UV Blocking*	Class 2	Class 1	Class 1	High Minus Sph powers	-6.50D to -9.00D (0.50D steps)	-6.50D to -9.00D (0.50D steps)
Visibility Tint	Yes	Yes	Yes	Cylindrical power	-0.75D, -1.25D and -1.75D	-0.75D, -1.25D, -1.75D, -2.25D and -2.75D
Inside Out Mark	ONLY Scribe marks at 6 & 12 o'clock	ONLY Scribe marks at 6 & 12 o'clock	ONLY Scribe marks at 6 & 12 o'clock	Axis	10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	10° to 180° (10° increments)
BC (mm) / Dia (mm)	8.50 / 14.5	8.60 / 14.5	8.60 / 14.5	Plus Sph powers	+0.25D to +4.00D (0.25D steps)	+0.25D to +6.00D (0.25D steps)
Power range (Refer to next table for cylinder axis)	Plano -0.25D to -9.00D +0.25D to +4.00D (in 0.50D steps above +/- 6.00D)	Plano -0.25D to -9.00D +0.25D to +6.00D (in 0.50D steps above +/- 6.00D)	Plano -0.25D to -9.00D +0.25D to +4.00D (in 0.50D steps above +/- 6.00D)	Cylindrical power	-0.75D, -1.25D and -1.75D	-0.75D, -1.25D, -1.75D, -2.25D and -2.75D
				Axis	10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	10° to 180° (10° increments)

*UV blocking : ANSI standards Class 1 : More than 99% UV-B and More than 90% UV-A

Class 2 : More than 95% UV-B and more than 70% UV-A