













## TECHNICAL SPECIFICATIONS

	SPHERICAL						TORIC		
	Daily Disposable			Reusable Disposable			Daily Disposable	Reusable Disposable	
ACUVUE® Products									
Pack size	30 lenses	90 lenses 30 lenses	30 lenses	12 lenses 6 lenses	6 lenses	6 lenses	30 lenses	6 lenses	6 lenses
<b>Lens Properties</b>									
Lens Material	senofilcon A	etafilcon A	narafilcon A	senofilcon A	etafilcon A	senofilcon C	etafilcon A	senofilcon A	senofilcon C
Water Content	38%	58%	46%	38%	58%	41%	58%	38%	41%
Oxygen Flux (Open Eye)	98%	88%	98%	98%	88%	98%	87%	98%	98%
Center Thickness @ -3.00D(mm)	0.085	0.084	0.085	0.070	0.084	0.70	0.090	0.080	0.080
UV Blocking*	Class 1	Class 2	Class 1	Class 1	Class 2	Class 1	Class 2	Class 1	Class 1
Visibility Tint	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Inside Out Mark	Yes	Yes ("123")	Yes ("123")	Yes ("123")	Yes ("123")	Yes ("123")			
Recommended Replacement	1 day	1 day	1 day	2 weeks	2 weeks	1 month	1 day	2 weeks	1 month
<b>Lens Specification</b>									
Lens Parameter BC (mm) / Dia (mm)	8.5 & 9.0/14.3	8.5 & 9.0 / 14.2	8.5 / 14	8.4 & 8.8 / 14.0	8.3 & 8.7 / 14.0	8.4 & 8.8 / 14.0	8.5 / 14.5	8.6 / 14.5	8.6 / 14.5
Full Power Range Spherical powers in Diopters	-0.50D to -6.00D (0.25D steps) -6.50D to -12.00D (0.50D steps) +0.50D to +6.00D (0.25D steps) +6.50D to +8.00D (0.50D steps)	-0.50 to -12.00 +0.50 to +6.00 0.50 to 6.00 (0.25D steps) 6.50 to -12.00 (0.50D steps)	-0.50 to -12.00 +0.50 to +6.00 0.50 to 6.00 (0.25D steps) 6.50 to -12.00 (0.50D steps)	Plano, -0.50 to -12.00 +0.50 to +8.00 0.50 to 6.00 (0.25D steps) 6.50 to -12.00 (0.50D steps)	-0.50 to -12.00 +0.50 to +8.00 0.50 to 6.00 (0.25D steps) 6.50 to -12.00 (0.50D steps)	-0.50 to -6.00 (0.25D steps) -6.50 to -12.00 (0.50D steps) +0.50 to +6.00 (0.25D steps) +6.50 to +8.00 (0.50D steps)	Plano to -9.00 +0.25 to +4.00	Plano to -9.00 +0.25 to +6.00	Plano to -9.00 +0.25 to +4.00
<b>Low to Mid Minus</b>									
Sph (in 0.25 steps)							Plano to -6.00D	Plano to -6.00D	Plano to -6.00D
Cylinder & Axis							Cyl: -0.75D, -1.25D, -1.75D Axis: 10° to 180° (in steps of 10) Cyl: -2.25D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° (in steps of 10)	Cyl: -0.75D, -1.25D, -1.75D Axis: 10° to 180° (in steps of 10) Cyl: -2.25D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°
<b>High Minus</b>									
Sph (in 0.50 steps)							-6.50D to -9.00D	-6.50D to -9.00D	-6.50D to -9.00D
Cylinder & Axis							Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° (in steps of 10)	Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°
<b>Plus Power</b>									
Sph (in 0.25 steps) Sph (in 0.50 steps)							+0.25D to +4.00D	+0.25D to +6.00D	+0.25D to +4.00D
Cylinder & Axis							Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° (in steps of 10)	Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°

\*UV Blocking : ANSI - Class 1: > 99% UVB > 90% UVA • Class 2: > 95% UVB > 70% UVA

The ACUVUE® family of products is the  
#1 Best Selling Contact Lenses in the World\*

For more details contact - Johnson & Johnson Vision Care  
Johnson & Johnson Pvt. Ltd. Arena Space, Near Majas Depot, J.V. Link Road, Jogeshwari (E), Mumbai 400 060. INDIA.  
Website: [www.acuvue.co.in](http://www.acuvue.co.in)

\* Euromonitor validated claim